3

164. (new): The passive safety mechanism of claim 163 wherein said slidable link has an arm which passes through said trigger and into said triggerbar.

5165. (new): The passive safety mechanism of claim 181 wherein said linkage provides an axle for said triggerbar to pivot about.

766. (new): In a firearm having a sear, a trigger, a triggerbar capable of rotation relative to said trigger, and a longitudinally slidable firing element; a passive safety mechanism comprising:

a. a blocking piece to block said firing element; and

b. a slidable linkage, distinct from said triggerbar, which connects said blocking piece to said trigger.

167. (new): The passive safety mechanism of claim 166 wherein said trigger is longitudinally slidable.

168 (new): The passive safety mechanism of claim 166 wherein said blocking piece is slidable.

169 (new): The passive safety mechanism of claim 106 wherein said slidable linkage comprises a slidable link.

170 (new): The passive safety mechanism of claim 166 wherein said blocking piece acts directly upon a sear catch of said firing element.

(new): The passive safety mechanism of claim 186 wherein a positive stop limits the maximum downward position of said blocking piece.

12172. (new): The passive safety mechanism of claim 171 wherein said positive stop comprises a mandrel for a torsion spring.

131. (new): In a firearm having a frame, a sear, a trigger, a triggerbar capable of rotation relative to said trigger, and a longitudinally slidable firing element; a passive safety mechanism comprising:

a. a blocking piece for blocking said firing element;

characterized in that rearward trigger motion cams said blocking piece to an unblocked position.

174. (new): The passive safety mechanism of claim 173 wherein said blocking piece has a transverse cantilever projection.

15 185. (new): The passive safety mechanism of claim 183 wherein a positive stop limits the maximum downward position of said blocking piece.

Cent

3

GAU 3641

Arnnt. J contd.

3

// 176. (new): The passive safety mechanism of claim 173 wherein said blocking piece is accessed for camming through a window in said frame.

(new): The passive safety mechanism of claim 178 wherein a camming stud engages a cam track.

178 (new): In a firearm having a sear, a trigger, a triggerbar capable of rotation relative to said trigger, and a longitudinally slidable firing element with a radial cantilever projection; a passive safety mechanism comprising:

a. a blocking piece for blocking said firing element;

characterized in that said blocking piece acts directly upon said projection.

179. (new): The passive safety mechanism of claim 178 wherein said projection extends downward.

20180. (new): The passive safety mechanism of claim 178 wherein said projection comprises a sear catch.

Grade